Declaration of performance

for the product

Secura Max Aquastop Smart



1.	Unique identification code of the product-type
	5905167734728 - Secura Max Aquastop Smart

	Type, batch or serial number or any other element allowing identification of the construction product as required under:					
۷.						
	EAN	5 905 167 734 728				

Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as fore

Insulating material for the acoustic use under floating floors

A. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant:

Decora S.A.; Prądzyńskiego 24a; 63-000 Środa Wielkopolska; Poland

Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

Not Applicable

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex

System number - 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard

No synchronized standard

8.	Declared performance						
Symbol	Parameter	Value		Unit	Norm		
Т	Thickness	5	+/- 0,40	[mm]	EN 823:2013		
L	Length	4700	-1% +5%	[mm]	EN 822:2013		
W	Width	1180	-1% +2,5%	[mm]	EN 822:2013		
Q	Squareness	< 5	0	[mm/m]	EN 824:2013		
S	Flatness	<2	0	[mm/m]	EN 825:2013		
AW	Surface mass	0,182	+/- 10%	[kg/m ²]	EN ISO 23997:2012		
QW	Density	36	+/- 10%	[kg/m ³]	EN 1602		
RWS	Reflected walking sound	10	+/-2	[%]	CEN/TS 16354:2013, EPLF 021029-3		
IS	Impact sound improvement	20	+/-2	[dB]	EN ISO 10140:2007		
CS	Compressive strength at 0.5 mm compression	90	+/- 10%	[kPa]	EN 826:2013		
CC	Static compressive strength	25	+/- 10%	[kPa]	EN 1606:2013		
DL	Dynamic compressive strength	> 500 000		[cycles]	EN 13793:2014		
PC	punctual conformability	4,6	+/- 10%	[mm]	EN ISO 868:2005		
TR	Thermal Resitance	0,18	+/- 0,003	[m ² K/W]	EN 12664:2002		
SD	sD-value	>150		[m]	EN 12086:2013		
RLB	Resistance to Large Ball	≤ 1600		[mm]	EN 438-2:2016		
RTF	Reaction on fire	[-]		[-]	EN 13501-1:2010		

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer

creation date	2021-11-30
modification date	2021-11-30
Printed	04.05.2022 09:48